





## 十三、DCY DCZ型减速机



DCY、DCZ型减速器外型尺寸

各义中心 距 <sub>a</sub>	a <sub>1</sub>	d <sub>1</sub>	l <sub>1</sub>	d <sub>2</sub>	l <sub>2</sub>	D	L	A	B	C	E	F	G	S	h	H	M
160	112	25	60	32	80	70	140	510	555	190	250	210	65	35	180	423	145
180	125	30	80	38		80	170	575	625	215	270	230	70		200	468	160
200	140	35		42	110	90		640	685	240	300	250	75	40	225	520	175
224	160	40	110	48		100	210	725	775	260	320	270	80	45	250	570	190
250	180	42		50		110		815	860	290	370	310	90	50	280	626	210
280	200	50		55		120		905	970	325	400	340	100	55	315	702	230
315	224	55	140	65	140	140	250	1020	1085	355	450	380	110	60	355	809	260
355	250	60		75		160	300	1140	1220	390	480	410	120	65	400	900	285
400	280	65		85	170	170		1275	1355	440	530	460	130	70	450	970	305
450	315	75	170	95		190	350	1425	1520	490	600	510	140	80	500	1065	345
500	355	90		100	210	220		1585	1690	570	650	560	150	90	560	1208	435
560	400	100		110		250	410	1775	1895	610	750	640	160	100	630	1325	475
630	450	110	210	130	250	300	470	1995	2145	675	800	690	170	110	710	1460	525
710	500	120		150		340	550	2235	2400	760	900	770	190	125	800	1665	570
800	560	130		160	300	400	650	2505	2700	840	1000	870	200	140	900	1870	625

各义中心 距 <sub>a</sub>	N-d <sub>1</sub>	N	P	R	K	T	b <sub>1</sub>	t <sub>1</sub>	b <sub>2</sub>	t <sub>2</sub>	b <sub>3</sub>	t <sub>3</sub>	平均重量 Kg	油量 l	图 号
160	6-18	30	115	210		495	8	28	10	35	20	74.5	200	9	DCY160.0(DCZ160.0)
180			135	240		565		33		41	22	85	255	13	DCY180.0(DCZ180.0)
200	6-23	35	145	255		615	10	38	12	45	25	95	325	18	DCY200.0(DCZ200.0)
224			165	290		705		43		51.5	28	106	453	26	DCY224.0(DCZ224.0)
250	6-27	40	180	315		780	12	45	14	53.5	28	116	586	33	DCY250.0(DCZ250.0)
280			200	355		880		53.5		59	32	127	837	46	DCY280.0(DCZ280.0)
315	8-33	50	220	405	655	985	16	59	18	69	36	148	1100	65	DCY315.0(DCZ315.0)
355		55	245	450		1110		64		79.5	40	169	1550	90	DCY355.0(DCZ355.0)
400			280	510		1245		69		90	40	179	1967	125	DCY400.0(DCZ400.0)
450	8-39	60	315	575	940	1400	20	79.5	25	100	45	200	3675	180	DCY450.0(DCZ450.0)
500		70	350	645		1550		95		106	50	231	4340	240	DCY500.0(DCZ500.0)
560	8-45	80	390	715	1165	1735	28	106	28	116	56	262	5320	335	DCY560.0(DCZ560.0)
630			445	800		1985		116		137	70	314	7170	480	DCY630.0(DCZ630.0)
710			500	900		2220		127		158	80	355	9600	690	DCY710.0(DCZ710.0)
800		90	560	1100		2520		137		169	90	417	13340	940	DCY800.0(DCZ800.0)

传动比代号及参数

1	2	3	4	5	6	7	8	9	10	11
16	18	20	22.4	25	28	31.5	35.5	40	45	50



# 减速传动 · 当选泰兴

中国名牌



DCY, DCYK型减速器承载能力

公称 传动比  i	公称转速 r/min		名义中心距 a														
			160	180	200	224	250	280	315	355	400	450	500	560	630	710	800
	输入 n1	输出 n2	公称输入功率 P <sub>1</sub> /kw														
16	1500	94	45	61	80	120	160	230	305	440	600	830	1350	1850	-	-	-
	1000	63	30	43	60	85	115	170	230	330	440	630	1010	1420	2200	2500	2850
	750	47	24	35	45	70	85	140	185	270	360	510	830	1180	1600	2300	2600
18	1500	83	42	58	75	110	150	210	290	440	560	780	1350	1850	-	-	-
	1000	56	30	40	53	75	105	155	215	330	420	590	1000	1400	1860	2500	2850
	750	42	23	32	42	65	80	120	175	260	345	480	790	1120	1460	2180	2500
20	1500	75	39	53	68	100	135	195	270	430	550	780	1320	1800	-	-	-
	1000	50	27	36	48	70	95	140	200	315	380	550	880	1240	1640	2400	2850
	750	38	20	28	38	55	75	110	160	245	310	445	700	1000	1290	1920	2500
22.4	1500	67	34	50	65	94	130	175	250	400	510	730	1170	1540	-	-	-
	1000	45	23	34	48	65	90	130	185	290	360	520	780	1100	1450	2120	2600
	750	33	17	25	36	49	70	95	140	220	275	400	620	880	1140	1710	2460
25	1500	60	30	44	62	83	115	160	225	350	450	650	1030	1460	-	-	-
	1000	40	20	30	42	57	80	110	165	255	315	460	730	1040	1350	2010	2600
	750	30	15	23	32	43	60	85	125	195	240	350	550	780	1010	1510	2180
28	1500	54	22	37	48	75	92	140	215	320	405	590	910	1290	-	-	-
	1000	36	15	25	34	52	66	94	150	225	285	420	640	910	1190	1770	2500
	750	27	12	19	26	39	50	71	115	170	215	315	490	690	890	1330	1920
31.5	1500	48	20	33	44	69	85	120	195	290	385	550	820	1170	-	-	-
	1000	32	14	22	31	46	59	83	130	200	255	370	580	820	1070	1600	2310
	750	24	10	17	23	34	44	62	100	150	190	280	440	620	800	1200	1740
35.5	1500	42	18	30	40	62	77	110	180	260	345	500	770	1100	1430	2120	-
	1000	28	12	20	28	42	53	75	120	180	230	340	510	720	950	1410	2030
	750	21	9	15	21	31	40	56	90	135	175	250	385	540	710	1060	1540
40	1500	38	17	27	36	56	69	98	160	235	310	450	690	990	1290	1920	-
	1000	25	11	18	25	41	47	67	120	160	225	330	465	660	860	1280	1850
	750	19	8.5	14	19	29	36	52	82	125	155	230	350	495	640	960	1390
45	1500	33.5	15	24	33	50	64	90	145	215	275	400	620	880	1150	1720	2100
	1000	22	10	16	22	33	42	60	95	145	180	265	455	640	840	1250	1810
	750	16.6	7.5	12	17	26	32	46	74	110	140	205	320	455	600	870	1260
50	1500	30	13	21	30	44	57	80	130	195	245	360	550	780	1030	1540	2050
	1000	20	9	14	20	31	38	54	87	130	165	240	365	520	680	1020	1480
	750	15	7	11	15	23	29	41	65	99	120	180	290	410	540	780	1130

注:1)需采用循环油润滑